




PH. 800-321-8073

FX. 334-855-3507



Model LB52-33

www.pittstrailers.com

STANDARD FEATURES

Load Capacity	104,000lbs. In 16'
Weight	18,400lbs.
Overall Length	45'
Width	8'6"
Deck Length	34' (31' Level Deck + 3' Dovetail)
Deck Height	33" Loaded
Gooseneck	Exposed Neck w/ Steel Motor Grader Ramps
Fifth Wheel Height	48"
King Pin Swing Radius	84"
King Pin Setting	18"
Mainframe	14" Wide Flange – Mill Roll "I" Beam
Siderails	12" Wide Flange-Mill Roll "I" Beam
Cross Members	8" Wide Flange-Mill Roll "I" Beam
Wheel Wells	Covered with Check Plate & Traction Bars
Dovetail	36" Covered with Check Plate & Traction Bars
Loading Ramps	Spring Assist, 24"x 72"
Landing Gear	Two Speed, 50,000lbs. Capacity
Lashing Rings	9 Per Side (18 total)
Decking	Full 1-3/4" Oak
Suspension	Hutch Three Point, Four Spring, with 14,000 lbs. Cap. Springs
Axles	25,000lbs. Capacity, 77.5" Track, Auto Slack Adjusters, Type 30 Brake Chambers, Outboard Drums
Brakes	12 1/4" x 7 1/2"
Tires	235/75R17.5 Low Profile Radials
Wheels	6.75 x 17.5 Steel Disc
Wiring	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box	Covered In Gooseneck
Mud Flaps	Spray Guard and Anti-Sail
Flag Holders	On All Four Corners
Paint	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

- Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) _____
- No Motor Grader Ramps _____
- 90° Gooseneck With Flat Upper Deck - Wood Filled _____

MAINFRAME – Fabricated "I" Beam with Positive Camber

DECK

- Additional Length In Deck Area _____
- Additional Width 9' includes 83.5" Track Axles _____
- 10' includes 95.5" Track Axles _____
- Widening Brackets _____
- Apitong 1- 3/4" (In Lieu of Oak) _____
- Floor Clips (In Lieu of Screws) _____

BOGIE

- o Type 30/30 Spring Brakes (per axle)
- o Aluminum Wheels (Outside Polished)
- o Air Ride 75,000 lb. Cap.
- o Dovetail Covered with Wood in Lieu of Check Plate
- o 48" Dovetail Covered with Check Plate & Traction Bars
- o 60" Dovetail Covered with Check Plate & Traction Bars
- o Rear Hydraulic Ramps (36" x 96")
 - o Double Folding (36" x 144")