

TA12 Standard Features



CAPACITY

24,000 lb. capacity at 55 MPH

ESTIMATED TARE WEIGH

6,250 lbs

DIMENSIONS

Overall: 102" width x 29' length

Platform: 34" height x 24' length

Dovetail: 60" length

Ramp: 23 1/2" width x 60" length

LOAD BASE

1 1/2" Premium Apitong

MAIN RAILS

W12" x 16# A572 Gr. 50 - High Tensile

CROSSMEMBERS

6" Jr. I-Beam A572 Gr. - High Tensile

AXLES

(2) Heavy Duty 12,000 lbs (2)

BRAKES

12 1/4" X 5" Electric

SUSPENSION

Heavy Duty H9700

TIRES

(8) 235/80R16 (E)

WHEELS

8 Hole, "Budd" Type Disc

ELECTRIC SYSTEM

Grote Ultra Blue™ - Sealed Wiring Harness -

Grote™ High Count LED Lights

HITCH

Adjustable Pintle Eye

LANDING GEAR

Heavy Duty Drop Leg 2-Speed

PAINT

Shot Blasted - Primed - Painted with PPG™

Automotive Grade Acrylic Urethane Top Coat

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.