

PT22 Standard Features



CAPACITY

55.000 lbs. GVWR

OVERALL LENGTH

22'

OVERALL WIDTH

102"

MAINBEAMS

14" Wide Flange Mill Roll I-Beams

SUSPENSION

3 Point, 4 Spring - 56,000 lb Capacity

AXLES

(2) 25,000 lb Capacity, 77 1/2" Track

49" Axle Spacings

Auto Slack

Anti Lock Brake System

16.5" x 7" Air Brakes

Type 30/30 Brake Chambers

WHEELS

Disc - Hub Piloted

TIRES

11R24.5 Radials

TANDEM SETTING

60" Standard

DRAW BAR

g.t.w. 60,000 lbs. - 3" Eye - 4 Position

TOUNGE

Continuation of Mainframe

SAFETY CHAIN

1/2" High Test

LANDING GEAR

Single Speed Drop Leg

BOLSTERS

(2) 4" x 10" x 102" Tubing, 70K Yield

BOLSTER SETTINGS

1-2: 12' | 3-4: None | 5-6: None | 7-8: None

STANDARDS

5" x 5" Tubing, 100K Yield

STANDARD HEIGHT

1st: 96" Overall | 2nd: 96" Overall | 3rd: None | 4th: None

5th: None | 6th: None | 7th: None | 8th: None

D. BOLSTER / RMV RISER

Dead Bolster

WINCHES

(2) 30' Nylon Straps and Handles on Frame

BUMPER

4" x 6" Tubing, 70K Yield

AIR TANK

Covered w/ Channel Iron

BRAKES

Type 30/30 Spring Brakes - 2 Axle

WIRING

D.O.T. sealed wiring harness

PROTECTIVE COATING

High quality 2-part black acrylic urethane

High quality 2-part primer

White blasted and cleaned prior to painting

OPTIONS

Revolver greaseless coupling system

Aluminum wheels

Grapple bar

Electronic or air scales

Single point spring suspension

PITTS-air lift axle on a single point suspension

Air ride suspension

Headboard

Slideable bolsters

Custom designs

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.

