

Carter



LB55-22GT · Hydraulic Detachable Gooseneck


PITTS *HEAVY HAUL*

APPROVED SOURCEWELL SUPPLIER

Sourcewell

Awarded Contract

Contract # 092922-PTT



Since 1976, Pitts has built trailers for the construction, commercial and forestry markets tough enough for every job and priced to make you profitable.

The workhorses of the heavy haul division, include a Hydraulic Detachable, Hydraulic Tail, Fixed Neck and Tag-Along with every feature you desire.

PITTS TRAILERS IS A SOURCEWELL APPROVED SUPPLIER



LB55-22GT Standard Features



CAPACITY
55 tons in 12' length (GAWR and tire ratings determine legal payloads)
ESTIMATED TARE WEIGHT (STANDARD PACKAGE)
22,544 lbs. +/- 3%
LOAD BASE
12' (In any given area in deck)
DIMENSIONS
Overall width: 8' 6" x 53' length
Clear deck length: 26'
Deck height under full load: 22" (ground clearance: 6")
50" nominal loaded 5th wheel height (5 ride height positions)
Rear bogie height: 41"
GOOSENECK DESIGN
Hydraulic, non ground bearing cantilever neck design, set up for wet line
5 Position adjustable ride height controls
Air locking pin
102" swing radius
DECK DESIGN
Main longitudinal members fabricated with 100 KSI yield steel flanges with 50 KSI yield webs
Level deck design
10" I-beam crossmember with 4" stub sill on 12" centers
1 1/2" nominal apitong
Front of deck approach ramp with traction cleats
Lockable toolbox in front of deck
Pull out style outriggers (extends trailer width 2')
BOGIE DESIGN
Fixed deck-to-bogie connection with front bogie ramp
V-style boom trough
Recessed load bearing bolsters between axles and behind last axle
Heavy-duty V-style rear bumper
Available fourth flip axle setup
Ultra low bucket well

AXLES
(3) Heavy-duty axles with 54 1/2" spread
25,000 lbs nominal capacity per axle (GAWR determined by suspension type, brakes, tires and other components)
Tapered spindle axles
BRAKES
16 1/2" x 7"
Heavy-duty brake drums, outboard mount
Automatic slack adjusters
Type 30/30 parking brakes on (2) axles
HUBS
Hub-piloted 10-stud mount
Outboard cast drums
WHEELS/TIRES
(12) Steel disc wheels 8.25 x 22.5 with 275/ 70R 22.5 H-ply tires
SUSPENSION
Unitized heavy duty 25,000 lbs, air-ride suspension with automatic and manual controls
Suspension override prevention straps on all axles
ELECTRICAL SYSTEM
Fully sealed wiring harness with LED lights
Marker lights and mid-turn signals
(3) Oval stop, tail and turn lights per side on rear
PROTECTIVE COATING
High quality 2-part PPG black acrylic urethane
High quality 2-part primer
White blasted and cleaned prior to painting
LASH RINGS
(8) Pair (16 total), bent D-ring
FLAG HOLDERS
(2) Pair (4 total)

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.

