





Since 1976, Pitts has built trailers for the construction, commercial and forestry markets tough enough for every job and priced to make you profitable.

The workhorses of the heavy haul division, include a Hydraulic Detachable, Hydraulic Tail, Fixed Neck and Tag-Along with every feature you desire.



## **TA25 Standard Features**



CAPACITY	SUSPENSION
50,000 lb. capacity at 55 MPH	Heavy Duty leaf spring
LOAD BASE	HUBS
16' concentrated load	Hub-piloted 8-stud mount
ESTIMATED TARE WEIGH	Outboard cast drums
10,850 lbs.	WHEELS
DIMENSIONS	(8) Hole, hub piloted
Overall: 102" width x 35' length	(8) 215/75x17.5 16 ply
Platform: 36" height x 29' length	ELECTRICAL SYSTEM
Dovetail: 60" length	Fully sealed wiring harness with LED lights
Ramp: 23 ½" width x 60" length	Marker lights and mid-turn signals
LOAD BASE	Oval stop, tail and turn lights per side on rear
1 ½" Premium Apitong	PROTECTIVE COATING
Wheel wells covered in steel with traction bars	High quality 2-part black acrylic urethane
Dovetail self cleaning ladder	High quality 2-part primer
Ramps self cleaning ladder	White blasted and cleaned prior to painting
MAIN RAILS	LASH RINGS
W14" x 26# A572 Gr. 50 - High Tensile	(4) Pair (8 total), bent D-ring
CROSSMEMBERS	нітсн
6" Jr. I-Beam A572 Gr. 50 - High Tensile	Adjustable Pintle Eye - 4 Position
AXLES	LANDING GEAR
(3) Heavy Duty 22,500 lbs 49" axle spacing	Heavy Duty Drop Leg 2-Speed
BRAKES	
12 ¼" X 7 ½" Air - ABS	

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.

CARTERMACHINERY.COM · 1330 Lynchburg Turnpike · Salem, VA · 24153 · 800-768-4200

