

**Carter**



LB55-22GT · Hydraulic Detachable Gooseneck


**PITTS** Trailers®  
Since 1976

APPROVED SOURCEWELL SUPPLIER

Sourcewell

Awarded Contract

Contract # 092922-PTT



Since 1976, Pitts has built trailers for the construction, commercial and forestry markets tough enough for every job and priced to make you profitable.

The workhorses of the heavy haul division, include a Hydraulic Detachable, Hydraulic Tail, Fixed Neck and Tag-Along with every feature you desire.

PITTS TRAILERS IS A SOURCEWELL APPROVED SUPPLIER



# LB55-22GT Standard Features



## CAPACITY

55 tons in 12' length (GAWR and tire ratings determine legal payloads)

## ESTIMATED TARE WEIGHT (STANDARD PACKAGE)

22,544 lbs. +/- 3%

## LOAD BASE

12' (In any given area in deck)

## DIMENSIONS

Overall width: 8' 6" x 53' length

Clear deck length: 26'

Deck height under full load: 22" (ground clearance: 6")

50" nominal loaded 5th wheel height (5 ride height positions)

Rear bogie height: 41"

## GOOSENECK DESIGN

Hydraulic, non ground bearing cantilever neck design, set up for wet line

5 Position adjustable ride height controls

Air locking pin

102" swing radius

## DECK DESIGN

Main longitudinal members fabricated with 100 KSI yield steel flanges with 50 KSI yield webs

Level deck design

10" I-beam crossmember with 4" stub sill on 12" centers

1 1/2" nominal apitong

Front of deck approach ramp with traction cleats

Lockable toolbox in front of deck

Pull out style outriggers (extends trailer width 2')

## BOGIE DESIGN

Fixed deck-to-bogie connection with front bogie ramp

V-style boom trough

Recessed load bearing bolsters between axles and behind last axle

Heavy-duty V-style rear bumper

Available fourth flip axle setup

Ultra low bucket well

## AXLES

(3) Heavy-duty axles with 54 1/2" spread

25,000 lbs nominal capacity per axle (GAWR determined by suspension type, brakes, tires and other components)

Tapered spindle axles

## BRAKES

16 1/2" x 7"

Heavy-duty brake drums, outboard mount

Automatic slack adjusters

Type 30/30 parking brakes on (2) axles

## HUBS

Hub-piloted 10-stud mount

Outboard cast drums

## WHEELS/TIRES

(12) Steel disc wheels 8.25 x 22.5 with 275/ 70R 22.5 H-ply tires

## SUSPENSION

Unitized heavy duty 25,000 lbs, air-ride suspension with automatic and manual controls

Suspension override prevention straps on all axles

## ELECTRICAL SYSTEM

Fully sealed wiring harness with LED lights

Marker lights and mid-turn signals

(3) Oval stop, tail and turn lights per side on rear

## PROTECTIVE COATING

High quality 2-part PPG black acrylic urethane

High quality 2-part primer

White blasted and cleaned prior to painting

## LASH RINGS

(8) Pair (16 total), bent D-ring

## FLAG HOLDERS

(2) Pair (4 total)

*Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.*