

## TA20 Standard Features



CAPACITY

40,000 lb. capacity at 55 MPH

**ESTIMATED TARE WEIGHT (STANDARD PACKAGE)** 

7,600 lbs.

**DIMENSIONS** 

Overall: 102" width x 30' length

Platform: 36" height x 24' length

Dovetail: 60" length

Ramp: 23 1/2" width x 60" length

LOAD BASE

16' concentrated load

**MAIN RAILS** 

W14" x 22# A572 Gr. 50 - High Tensile

LOAD BASE

Deck 1 1/2" Premium Apitong

Wheel wells covered in steel with traction bars

Dovetail self cleaning ladder

Ramps self cleaning ladder

AXLES

(2) Heavy Duty 22,500 lbs 49" axle spacing

BRAKES

12 1/4" x 7 1/2" air-ABS

SUSPENSION

Heavy duty leaf spring

HUBS

Hub-piloted 8-stud mount

Outboard cast drums

WHEELS/TIRES

(8) Hole, hub piloted

(8) 215/75x17.5 16 ply

**ELECTRICAL SYSTEM** 

Fully sealed wiring harness with LED lights

Marker lights and mid-turn signals

Oval stop, tail and turn lights per side on rear

PROTECTIVE COATING

High quality 2-part black acrylic urethane

High quality 2-part primer

White blasted and cleaned prior to painting

HITCH

Adjustable Pintle Eye - 4 Position

LANDING GEAR

Heavy Duty Drop Leg 2-Speed

LASH RINGS

(4) Pair (8 total), bent D-ring

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2019 Pitts Enterprises, Inc. (published). All rights reserved.





